



SpekTrix Sub

A compact sub-bass loudspeaker designed to provide high SPL low-end extension to SpekTrix line array loudspeakers. It is equipped with two powerful 18" Kevlar cone drivers in a tuned and vented enclosure. The SpekTrix Sub features convertible cardioid technology. It can be arrayed conventionally (all enclosures facing the same way) or in front-back or front-back-front setups for true cardioid performance.

Four sets of captured, precision-machined aluminum rigging hardware are spring-loaded and retract into the body when not in use. Four NL8 connectors (two front, two back) enable easy cable loop-thru regardless of the cabinet orientation.

Specifications

Frequency Range (+/- 3dB)	35Hz - 110Hz
Maximum Peak SPL **	138 dB
Components LF	2x AW18 18" Kevlar Driver
Nominal Impedance LF	4 Ω
Power Handling (AES / Peak) LF	2x 600 / 2x 2400 W
Rigging	Spring-Loaded Rigging Hardware pops up from the top of the sub in four slots. This allows for SpekTrix cabinets to easily be attached under a SpekTrix sub in an array.
Connection	4x Speakon™ NL8: 2x Front (Pins 2 +/-), 2x Rear (Pins 1 +/-)
Height Front (mm / in)	588 / 23.1
Width (mm / in)	710 / 28
Depth (mm / in)	820 / 32
Weight (kg / lbs)	77 / 170
Supported Processing	Lake, XTA

**12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

