product specifications





- HIGH SOUND PRESSURE LEVELS
- FOR USE IN 3 & 4 WAY SYSTEMS
- FREQUENCY RESPONSE OF 35 200Hz
- COMPACT AND VERSATILE DESIGN

Designed as a companion to our SX series line of full-range speaker enclosures, the SXsub has proven itself to be worthy of any extended low frequency response duty. Capable of extremely high SPI, this enclosure is the perfect match when used in conjunction with other Adamson enclosures - extending low-end frequency response to below 30Hz. The SXsub is equipped with 2 AW18 Kevlar bass drivers mounted in a tuned, vented and heavily braced cabinet. Supplied with integral castors for easy tilt and roll, this cabinet is lightweight, compact and powerful.







technical specifications





DESCRIPTION

Compact, easily transported, sub bass loudspeaker, designed to provide high SPL extended bass to all Adamson fullrange enclosures. The SXsub is equipped with two, AW18 Kevlar bass drivers in a tuned, vented enclosure. Integral Tilt & Roll castors are supplied as standard equipment.

APPLICATIONS

- Live Concert Reproduction
- Drum Fill & Side Fill Monitoring
- Theatres
- Houses of Worship

FEATURES

- Twin 18 Kevlar Bass Drivers
- Frequency Response of 30 200Hz
- Compact
- Durable Dual Component Finish
- Computer Punched Steel Grille
- Roadworthy Construction

PRODUCT DATA	
Dimensions & Weight (Inch & Lbs) Height Width	<u>42</u> 24.625
Depth Weight (<i>Kg</i>)	24.5 135 (61.4)
Finish	Black Dual Component Synthetic Resin
Accesories	2 x Heavy Duty Urethane Wheels
Cabinet Construction	Rugged 5/8 (15mm) Baltic Birch

TECHNICAL DATA	
Frequency Response (Hz)	35Hz to 200 Hz
Max Continuous SPL (dB)	124
Peak SPL (dB)	130
LF Section	2 AW18 Kevlar Low Freq.
	Transducers
Sensitivity (dB SPL@1Watt/1m)	
LF	100
Power Handling (Watts RMS)	
LF	600 (2)
LF Peak	1200 (2)
Connection	Neutrik Speakon NL4

Specifications Are Subject To Change Without Notice





